



Marchio/Brand

Tecfrigo

Articolo/Article

U51AXY-13CAC

Modello/Model

KARINA 137 Q-SS



ATTENZIONE: IMMAGINE PURAMENTE INDICATIVA, ACCESSORI ED OPTIONAL NON INCLUSI/ATTENTION: THE PHOTO IS PURELY INDICATIVE, ACCESSORIES AND OPTIONALS NOT INCLUDED

Use, Configuration and General Features

Categoria prodotto/Product category	Horizontal Displays
Specifiche/Specific	free installation, transition 4.0
Colori Standard/Standard colors	Black color
Colori Optional/Optional colors	RAL color bottom panels
Serratura/ Locks	Optional
Luce interna/ Internal light	LED
Dotazione Interna/Internal Equipment	3
Tipologia dotazione/Equipment type	395x1270
Descrizione Dotazione/Equipment Description	Glass Shelves

Operating Conditions and Climate Class

Temperatura di funzionamento/Working temperature /T°	+6/+9
Temperatura di funzionamento vano 2/2nd Compartment Working temperature /T°	N.A.
Classe climatica/Climatic class	3
Temperatura classe climatica/Climate class temperature/T°	25
Umidità classe climatica/Humidity climatic class	0,6

Dimensions, Weight and Capacity

Dimensioni LxPxH/Dimensions LxDxH /mm	1340x725x1340
Peso Netto/Net weight/Kg	214
Dimensioni con imballo LxPxH/dimensions with package LxDxH/mm	1440x870x1730
Peso Lordo/Gross weight/Kg	244
Capacità (L)/ Capacity /Lt.	550

Electrical Data and Energy Components

Tensione/ Tension /Volt	230
Frequenza (Hz)/Frequency (Hz):/Hz	50
Corrente nominale (Ampere)/Nominal current (amps)/Ampere	2, 65
Potenza/ Power /Kwatt	0, 58
Potenza Resistenze/Power resistance	0
Potenza Lampade/Power lamps	0

Refrigeration System and Performance

Gas refrigerante/ Cooling gas	R290
Carica del gas (kg)/Gas charge/Kg	0, 12
Refrigerazione/ Refrigeration	Ventilated
Refrigerazione vano 2/ 2nd Compartment Refrigeration	N.A.
Sbrinamento/ Defrosting	Automatic Hot Gas
Sbrinamento vano 2/ 2nd Compartment Defrosting	N.A.
Evaporazione acqua di sbrinamento/ Evaporation of defrost waer	AUT
Umidità/Humidity	70
Umidità vano 2/2nd Compartment humidity	N.A.
Numero compressori/Compressors number	1
Potenza frigorifera/Refrigeration power	0
Pressione di collaudo/Testing pressure/Bar	30

OPTIONALS

Modello

Verniciatura RAL profili inferiori vetrate e contorno porte/RAL painting lower glass profiles and door frame

Vetri per altitudine/Glasses suitable for altitude

Vetro laterale singolo riscaldato/Single heated side glass

Verniciatura RAL porte battenti/RAL painting for hinged doors

Colore Ral pannelli inferiori/RAL color bottom panels

ACCESSORIES

Codice acc / Modello