



Marchio/Brand

Tecfrigo

Articolo/Article

EA1AXY-13AAC

Modello/Model

KARINA 187 Q M



ATTENZIONE: IMMAGINE PURAMENTE INDICATIVA, ACCESSORI ED OPTIONAL NON INCLUSI/ATTENTION: THE PHOTO IS PURELY INDICATIVE, ACCESSORIES AND OPTIONALS NOT INCLUDED

Use, Configuration and General Features

Categoria prodotto/Product category	Horizontal Displays
Specifiche/Specific	sliding doors, free installation, paintable_RAL, Normal Temperature, Pastry & Bakery, Deli, transition 4.0
Colori Standard/Standard colors	Black
Colori Optional/Optional colors	low panel RAL
Serratura/ Locks	Optional
Luce interna/ Internal light	LED
Dotazione Interna/Internal Equipment	4
Tipologia dotazione/Equipment type	395x865
Descrizione Dotazione/Equipment Description	Glass Shelves

Operating Conditions and Climate Class

Temperatura di funzionamento/Working temperature /T°	+4/+10
Temperatura di funzionamento vano 2/2nd Compartment Working temperature /T°	N.A.
Classe climatica/Climatic class	4
Temperatura classe climatica/Climate class temperature/T°	30
Umidità classe climatica/Humidity climatic class	55%

Dimensions, Weight and Capacity

Dimensioni LxPxH/Dimensions LxDxH /mm	1800x710x1150
Peso Netto/Net weight/Kg	0
Dimensioni con imballo LxPxH/dimensions with package LxDxH/mm	1900x870x1730
Peso Lordo/Gross weight/Kg	40
Capacità (L)/ Capacity /Lt.	560

Electrical Data and Energy Components

Tensione/ Tension /Volt	230
Frequenza (Hz)/Frequency (Hz):/Hz	50
Corrente nominale (Ampere)/Nominal current (amps)/Ampere	3, 6
Potenza/ Power /Kwatt	0, 63
Potenza Resistenze/Power resistance	N.A
Potenza Lampade/Power lamps	N.A

Refrigeration System and Performance

Gas refrigerante/ Cooling gas	R290
Carica del gas (kg)/Gas charge/Kg	0, 120
Refrigerazione/ Refrigeration	Ventilated
Refrigerazione vano 2/ 2nd Compartment Refrigeration	N.A.
Sbrinamento/ Defrosting	Automatic Pause
Sbrinamento vano 2/ 2nd Compartment Defrosting	N.A.
Evaporazione acqua di sbrinamento/ Evaporation of defrost waer	AUT
Umidità/Humidity	70
Umidità vano 2/2nd Compartment humidity	N.A.
Numero compressori/Compressors number	1
Potenza frigorifera/Refrigeration power	N.A
Pressione di collaudo/Testing pressure/Bar	30

OPTIONALS

Modello

Condensazione ad acqua/Condensation by water

Rotazione parte superiore interna per versione telaio alluminio/Rotation of the upper internal part for aluminium frame version

Rotazione parte superiore per avere porte lato cliente e cruscotto comandi lato operatore con uso telaio alluminio/Upper part rotation to have doors on the customer side and control panel on the operator side for aluminium frame version

Serigrafia vetri in colore bianco/Glasses with white silk-screen

Serratura (per ogni porta)/Lock (for every door)

Telaio con profili in alluminio/Frame with aluminium profiles

Verniciatura RAL per telaio con profili in alluminio (le porte non vengono verniciate)/RAL painting for aluminium profile frame (doors won't be painted)

Verniciatura RAL profili inferiori vetrate e contorno porte/RAL painting lower glass profiles and door frame

Vetri per altitudine/Glasses suitable for altitude

Kit porte scorrevoli lato cliente con uso telaio in alluminio/Sliding doors on customer side for aluminium frame version

Vetro laterale singolo riscaldato/Single heated side glass

Colore Ral pannelli inferiori/RAL color bottom panels

ACCESSORIES

Codice acc / Modello

