



Marchio/Brand

Tecfrigo

Articolo/Article

Y62AXY-13CAC

Modello/Model

MEAT 360 DA FG



ATTENZIONE: IMMAGINE PURAMENTE INDICATIVA, ACCESSORI ED OPTIONAL NON INCLUSI/ATTENTION: THE PHOTO IS PURELY INDICATIVE, ACCESSORIES AND OPTIONALS NOT INCLUDED

Use, Configuration and General Features

Categoria prodotto/Product category	Meat & Fish
Specifiche/Specific	free installation, transition 4.0, maturation, Butcher's
Colori Standard/Standard colors	Black color
Colori Optional/Optional colors	
Serratura/ Locks	STANDARD
Luce interna/ Internal light	LED
Dotazione Interna/Internal Equipment	2
Tipologia dotazione/Equipment type	514x402
Descrizione Dotazione/Equipment Description	Wire Shelves

Operating Conditions and Climate Class

Temperatura di funzionamento/Working temperature /T°	+1/+2
Temperatura di funzionamento vano 2/2nd Compartment Working temperature /T°	N.A.
Classe climatica/Climatic class	4
Temperatura classe climatica/Climate class temperature/T°	30
Umidità classe climatica/Humidity climatic class	0,55

Dimensions, Weight and Capacity

Dimensioni LxPxH/Dimensions LxDxH /mm	595x595x1858
Peso Netto/Net weight/Kg	83
Dimensioni con imballo LxPxH/dimensions with package LxDxH/mm	640x680x2150
Peso Lordo/Gross weight/Kg	91
Capacità (L)/ Capacity /Lt.	368

Electrical Data and Energy Components

Tensione/ Tension /Volt	230
Frequenza (Hz)/Frequency (Hz):/Hz	50
Corrente nominale (Ampere)/Nominal current (amps)/Ampere	2, 33
Potenza/ Power /Kwatt	0, 35
Potenza Resistenze/Power resistance	0
Potenza Lampade/Power lamps	0

Refrigeration System and Performance

Gas refrigerante/ Cooling gas	R290
Carica del gas (kg)/Gas charge/Kg	0, 05
Refrigerazione/ Refrigeration	Ventilated
Refrigerazione vano 2/ 2nd Compartment Refrigeration	N.A.
Sbrinamento/ Defrosting	Automatic Hot Gas
Sbrinamento vano 2/ 2nd Compartment Defrosting	N.A.
Evaporazione acqua di sbrinamento/ Evaporation of defrost waer	AUT
Umidità/Humidity	50/80 Adjustable
Umidità vano 2/2nd Compartment humidity	N.A.
Numero compressori/Compressors number	1
Potenza frigorifera/Refrigeration power	0
Pressione di collaudo/Testing pressure/Bar	30

Temperatura ambiente consigliata tra 20°C e 30°C e umidità 55% / Recommended ambient temperature between 20° C and 30° C and humidity 55%

OPTIONALS

Modello

Kit luce Led rosa/Pink Led light

Sistema di controllo remoto (WiFi/Cloud)/Remote control system (WiFi/Cloud)

Vetri per altitudine/Glasses suitable for altitude

ACCESSORIES

Codice acc / Modello

V670301 / Vassoio 400x200mm/Tray 400x200mm