



Marchio/Brand

Tecfrigo

Articolo/Article

AC5A-0-13AAC

Modello/Model

**SNELLE WINE 251 SG
NE**



ATTENZIONE: IMMAGINE PURAMENTE INDICATIVA, ACCESSORI ED OPTIONAL NON INCLUSI/ATTENTION: THE PHOTO IS PURELY INDICATIVE, ACCESSORIES AND OPTIONALS NOT INCLUDED

Use, Configuration and General Features

Categoria prodotto/Product category	Wine
Specifiche/Specific	sliding doors, built-in, paintable_RAL, without group, Normal Temperature, Wine
Colori Standard/Standard colors	Black color
Colori Optional/Optional colors	RAL color
Serratura/ Locks	N.A.
Luce interna/ Internal light	LED
Dotazione Interna/Internal Equipment	2
Tipologia dotazione/Equipment type	676X255 (72 BOTT.DIAM.75 mm)
Descrizione Dotazione/Equipment Description	Glass Shelves

Operating Conditions and Climate Class

Temperatura di funzionamento/Working temperature /T°	+4/+10
Temperatura di funzionamento vano 2/2nd Compartment Working temperature /T°	+5/+16
Classe climatica/Climatic class	4
Temperatura classe climatica/Climate class temperature/T°	30
Umidità classe climatica/Humidity climatic class	55%

Dimensions, Weight and Capacity

Dimensioni LxPxH/Dimensions LxDxH /mm	800x400x1075
Peso Netto/Net weight/Kg	61
Dimensioni con imballo LxPxH/dimensions with package LxDxH/mm	910x700x1360
Peso Lordo/Gross weight/Kg	70
Capacità (L)/ Capacity /Lt.	250

Electrical Data and Energy Components

Tensione/ Tension /Volt	230
Frequenza (Hz)/Frequency (Hz):/Hz	50
Corrente nominale (Ampere)/Nominal current (amps)/Ampere	0, 15
Potenza/ Power /Kwatt	0, 05
Potenza Resistenze/Power resistance	0
Potenza Lampade/Power lamps	0

Refrigeration System and Performance

Gas refrigerante/ Cooling gas	R134A
Carica del gas (kg)/Gas charge/Kg	0, 01
Refrigerazione/ Refrigeration	Agitated
Refrigerazione vano 2/ 2nd Compartment Refrigeration	N.A.
Sbrinamento/ Defrosting	Automatic Pause
Sbrinamento vano 2/ 2nd Compartment Defrosting	N.A.
Evaporazione acqua di sbrinamento/ Evaporation of defrost waer	MAN
Umidità/Humidity	70
Umidità vano 2/2nd Compartment humidity	N.A.
Numero compressori/Compressors number	0
Potenza frigorifera/Refrigeration power	450
Pressione di collaudo/Testing pressure/Bar	30

OPTIONALS

Modello

SG: valvola solenoide/SG: Solenoid valve

Vetri per altitudine/Glasses suitable for altitude

Colore Ral/RAL color

ACCESSORIES

Codice acc / Modello

X19369MAT / Motore remoto predisposto a valvola/Remote compressor prearranged for valve