



Marchio/Brand

Tecfrigo

Articolo/Article

F56A-0-02CAC

Modello/Model

STYLE SG VFS



ATTENZIONE: IMMAGINE PURAMENTE INDICATIVA, ACCESSORI ED OPTIONAL NON INCLUSI/ATTENTION: THE PHOTO IS PURELY INDICATIVE, ACCESSORIES AND OPTIONALS NOT INCLUDED

Use, Configuration and General Features

Categoria prodotto/Product category	Drop-In
Specifiche/Specific	sliding doors, built-in, without group, Normal Temperature
Colori Standard/Standard colors	Silver color
Colori Optional/Optional colors	Bronze color
Serratura/ Locks	N.A.
Luce interna/ Internal light	LED
Dotazione Interna/Internal Equipment	2
Tipologia dotazione/Equipment type	1200x520
Descrizione Dotazione/Equipment Description	Plexiglass Shelves

Operating Conditions and Climate Class

Temperatura di funzionamento/Working temperature /T°	+4/+10
Temperatura di funzionamento vano 2/2nd Compartment Working temperature /T°	N.A.
Classe climatica/Climatic class	3
Temperatura classe climatica/Climate class temperature/T°	25
Umidità classe climatica/Humidity climatic class	0, 6

Dimensions, Weight and Capacity

Dimensioni LxPxH/Dimensions LxDxH /mm	1423x750x845
Peso Netto/Net weight/Kg	115
Dimensioni con imballo LxPxH/dimensions with package LxDxH/mm	1510x810x1240
Peso Lordo/Gross weight/Kg	139
Capacità (L)/ Capacity /Lt.	0

Electrical Data and Energy Components

Tensione/ Tension /Volt	230
Frequenza (Hz)/Frequency (Hz):/Hz	50
Corrente nominale (Ampere)/Nominal current (amps)/Ampere	0, 6
Potenza/ Power /Kwatt	0, 1
Potenza Resistenze/Power resistance	0
Potenza Lampade/Power lamps	0

Refrigeration System and Performance

Gas refrigerante/ Cooling gas	R452A
Carica del gas (kg)/Gas charge/Kg	0, 01
Refrigerazione/ Refrigeration	Ventilated
Refrigerazione vano 2/ 2nd Compartment Refrigeration	N.A.
Sbrinamento/ Defrosting	Automatic Pause
Sbrinamento vano 2/ 2nd Compartment Defrosting	N.A.
Evaporazione acqua di sbrinamento/ Evaporation of defrost waer	MAN
Umidità/Humidity	70
Umidità vano 2/2nd Compartment humidity	N.A.
Numero compressori/Compressors number	0
Potenza frigorifera/Refrigeration power	700
Pressione di collaudo/Testing pressure/Bar	30

OPTIONALS

Modello

Kit porte scorrevoli lato cliente/Sliding doors on customer side

Porta self-service lato cliente/Self-service door on customer side

SG: valvola solenoide/SG: Solenoid valve

Colore Bronzo/Bronze color

ACCESSORIES

Codice acc / Modello

X19644MAT / Motore remoto predisposto a valvola/Remote compressor prearranged for valve

X03181 / Kit mezzo pianetto inox/S/S small top